



## primesolution

**Odourless Synthetic Interior Primer  
15150**



### COMPLIANCE INDICATORS

at 05/30/2016

E.C. VOC Cat 39

### DESCRIPTION

A premium quality interior synthetic primer for use on new or previously painted surfaces including finished millwork, plywood, particle boards, oriented strand board, and dimensioned lumber. Formulated for blocking stains, fire and smoke damaged surfaces as well as for blocking tannin bleed when painting redwood and cedar. Also recommended for use on drywall, plaster, masonry, brick, painted metal and most other glossy surfaces. May be used under both latex and oil base paints.

### RECOMMENDED USES

A premium quality interior synthetic primer for use on new or previously painted surfaces including finished millwork, plywood, particle boards, oriented strand board, and dimensioned lumber. Formulated for blocking stains, fire and smoke damaged surfaces as well as for blocking tannin bleed when painting redwood and cedar. Also recommended for use on drywall, plaster, masonry, brick, painted metal and most other glossy surfaces. May be used under both latex and oil base paints.

### FEATURES

- › Excellent Interior primer/sealer
- › Low odour application
- › Rapid re-coat
- › Blocks cedar and redwood bleed
- › Seals smoke, nicotine and water stains
- › Excellent adhesion to various substrates
- › VOC compliant

### TECHNICAL CHARACTERISTICS

Bases	VOC(g/L)*
-------	-----------

White Primer (15150)	< 350
----------------------	-------

*\*Before thinning and the addition of colorants*

### FINISH

Gloss Category: Gloss Level 0 - Primer-Sealer-Undercoat

### SOLIDS & DENSITY

Volume: 55%

Weight: 77%

Density: 15.29 lbs per gallon. Container extra

### FILM THICKNESS (PER COAT)

Wet: 3.2 - 3.6 mils (81 - 91 microns)

Dry: 1.8 - 2.0 mils (46 - 51 microns)

### THEORETICAL COVERAGE (PER COAT)

440 - 490 ft<sup>2</sup> per gallon (41 - 46 m<sup>2</sup>/L)

### DRYING TIME

at 25°C (77°F) and 50% Relative Humidity

To Touch: 30 minutes

To Recoat: 2 hours

To Dry: 6 hours

### CLEAN UP

Clean tools and equipment with mineral spirits.





# Cloverdale Paint TECHNICAL DATA SHEET

## SURFACE PREPARATION

**Surface preparation is important.** All surfaces must be smooth, clean, dry, free of mildew, grease, soap film, sanding dust or other contaminants. Remove all loose or peeling material from previously-painted surfaces. Wash all surfaces with a solution of 3 tablespoons of (Phosphate-free) TSP in a gallon of warm water. Rinse thoroughly, allow to dry and then scuff sand using 80-120 grit sandpaper on a hand sander. Remove all sanding dust. Do not apply at temperatures below 5°C (40°F).

**WARNING!** If you scrape, sand or remove old lead paint from any surface you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. For additional information, Canadian customers contact the Product Safety division of Health Canada at 1-800-O-CANADA, US customers contact the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323).

## APPLICATION

Apply only in dry conditions. Apply when surface and ambient temperature is between 5°C (40°F) and 30°C (86°F). Temperatures must remain in this range for at least 4 hours after application. Do not apply when relative humidity is above 85%.

### Application Equipment

Stir well before and during use. Best results are achieved when using premium quality lint free rollers or natural bristle brushes. Always apply coating at the recommended spread rate. Check with vendor representative for spray application techniques. Recommended tip sizes: 0.013" - 0.017". Use a nylon/synthetic brush, roller, pad or sprayer. Back roll with spray application. Use appropriate applicator for the specific job.

## SAFETY PRECAUTIONS

*For detailed information please refer to SDS*

### READ LABEL AND SAFETY DATA SHEET PRIOR TO USE.

#### Recent Amendments

Check for recent amendments to this data sheet at [www.cloverdalepaint.com](http://www.cloverdalepaint.com)

**Last Modification date:** 08/12/2025

## LIMITATION OF LIABILITY

To the best of our knowledge, the technical data contained herein are true and accurate at the time of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. All technical advice, recommendations and services regarding this product are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from this product use by Buyer whether as recommended herein or otherwise. Such recommendations, technical advice or services are not to be taken as a license to operate under or suggest infringement of any patent.

## WARRANTY

Cloverdale Paint Inc. warrants its products to be free from defects in material and workmanship. At its option, Cloverdale Paint Inc. will either replace products not conforming to this warranty or credit the Buyer's account the invoiced amount for the non-conforming products. This is Cloverdale Paint Inc.'s sole obligation and Buyer's exclusive remedy in connection with the products. In no event shall Cloverdale Paint Inc. be liable for special, indirect, consequential or incidental damages.

By purchasing this product the Buyer accepts this warranty in lieu of all others, and waives all claims to any other remedy arising from any warranty or guarantee of quality, whether such warranty or guarantee of quality was made expressly to the Buyer or implied by any applicable law.

Any claim under this warranty must be made in writing by the Buyer to Cloverdale Paint Inc. within ten (10) days of discovery of the claimed non-conformance, but in no event later than one (1) year from the delivery date. The Buyer's failure to notify Cloverdale Paint Inc. of such non-conformance as required herein shall bar the Buyer from recovery under this warranty.



**Cloverdale Paint**

400 - 2630 Croydon Drive, Surrey, BC Canada V3Z 6T3  
Tel: 604.596.6261 [www.cloverdalepaint.com](http://www.cloverdalepaint.com)



Proudly Canadian Owned & Operated

Page 2 of 2  
Product: 15150  
Printed: 09/16/2025  
Version: 08/12/2025